

Specifications of L10 V2	
General specifications	
Total weight (W/O batteries)	13.9 kg
Max. take-off weight	29 kg
Dimensions (arms & propellers unfolded)	1460 x 1020 x 670 [mm]
Dimensions (arms unfolded, propellers folded)	1380 x 940 x 670 [mm]
Dimensions (arms and propellers folded)	780 x 500 x 670 [mm]
Max. hovering time	26 min (18 kg) 12.5min (29 kg)
GPS	GPS, GLONASS, Galileo, Emlid LoRa 868Mhz
Heading	Dual-RTK
Hovering precision	±10 cm (RTK) ±2m (without RTK)
Rotor dimensions	30 x 11
Battery type	Li-Po Smart
Battery capacity	16000 mAh
Battery voltage	43.5V
Battery weight	4.2 kg
Battery charging time	min. 11 minutes
Battery charger	4 ports (2 balance)
Battery charger power	3000 W
CDA Spraying System	
Maximum per Hectare Performance	10 ha/h
Average per Hectare Performance	6-8 ha/h
CDA technology	Rotating disc
Spraying advantage	Non-pressurized and low drift

Spray tank capacity	10
Number of Nozzles	2
Adjustable droplet size	60 – 1000 µm
Adjustable working width	1.5 - 6 m
Pump type	Membrane
Maximum flow	5L/min
Spreading system compatibility	
Seeder & Spreader	22 L
Trichogramma	8 L
Execution of work	
Technology developed for European Agricultural conditions	
Intrusion protection	Limited water and dust resistance
Easy transportability	
Modular payload attachability	
Obstacle detection and collision avoidance	3D, LiDAR based (ABZ sense)
FPV camera	Wide angle, vertically adjustable (0-180°)
Camera resolution	FHD
Effective signal range of RC	3,5 km
Altitude measurement	LIDAR
Flight planning	
Software source code	Open
Spot spraying	

Area and polyline shapefile import	
Software compatibility	Multiple
RTK base	Optional Emlid RS mobile base station
Data security	
No data transmission to remote servers	
Frequency bands	
Radio Control and Telemetry	2.4GHz
WLAN	2.4GHz
Flight	
Max. pitch angle	30°
Max. operating flight speed	7 m/s
Max. level speed	15 m/s
Max. flight altitude (AMSL)	4500 m
Max. flight altitude (AGL)	120 m
Max. tolerable wind speed	10 m/s