


Specifications of M40		
General specifications		
	EU	US
Payload	max. 36 kg	max. 79 lbs
Max. take-off weight	72 kg	158.7 lbs
Total weight (with battery) *	36 kg	79 lbs
Total weight (without battery) *	26 kg	57.1 lbs
Maximum characteristic dimension **	3130 mm	123.2 in
Dimensions (arms & propellers unfolded) (L x W x H)	2490 x 2600 x 700 mm	98 x 102.4 x 27.6 in
Dimensions (arms and propellers folded) (L x W x H)	1040 x 685 x 700 mm	41 x 27 x 27.6 in
Maximum flight time	15-20 minutes (standard) max. 40 minutes (custom development)	15-20 minutes (standard) max. 40 minutes (custom development)
GNSS	GPS, GLONASS, Galileo, BeiDou	GPS, GLONASS, Galileo, BeiDou
RTK correction	Network RTK Optional Emlid RS RTK base station	Network RTK Optional Emlid RS RTK base station
Hovering precision	±10 cm (RTK) ±1.5 m (without RTK)	±3.93 in (RTK) ±59 in (without RTK)

Heading	Dual-RTK	Dual-RTK
Rotor dimensions	30 x 11	30 x 11
Battery type	Li-Po Smart	Li-Po Smart
Battery capacity	30000 mAh	30000 mAh
Battery voltage (nominal)	53.2V	53.2V
Battery weight	9.9 kg	21.8 lbs
Battery charging time	min. 15 minutes	min. 15 minutes
Battery charger channels	2 x 4 ports	2 x 4 ports
Battery charger power	2 x 3000 W	2 x 3000 W
Camera	Wide angle, vertically adjustable (0-180°)	Wide angle, vertically adjustable (0-180°)
Camera resolution	FHD	FHD
Effective signal range of RC	~3.5 km	~2.17 mi
Altitude control	Barometric, GPS, LiDAR(Optional)	Barometric, GPS, LiDAR(Optional)
Obstacle detection and collision avoidance	Optional	Optional
Intrusion protection	Limited water and dust resistance	Limited water and dust resistance
Payload connections		
Power source	5V, 12V, Battery voltage	5V, 12V, Battery voltage
Communication ports	I2C, UART, CAN, USB	I2C, UART, CAN, USB

Signal inputs/outputs	PWM, GPIO	PWM, GPIO
Frequency bands		
Radio Control and Telemetry	2.4GHz	2.4GHz
WLAN	2.4GHz	2.4GHz
LoRA	862–1020 MHz	862–1020 MHz
Flight		
Max. pitch angle	15°	15°
Max. operating flight speed	8 m/s	8.9 mi/h
Max. level speed	10 m/s	22.4 mi/h
Max. flight altitude (AMSL)	4500 m	14763.78 ft
Max. flight altitude (AGL)	120 m	393.7 ft
Max. tolerable wind speed	10 m/s	22.4 mi/h
EMC Certificates		
FCC IDs	2ABCB-RPI5, XPYANNAB4, 2BN8IUNIRC7RFMD, RID-LR101H	
CE		

*The weight parameters vary by ±1kg according to the final product configuration

*The weight parameters vary by ±2.2 lbs according to the final product configuration

** Maximum distance between the tips of two opposite propellers